



# Halogen non-reflector

5761 30W G4 6V 1CT

Halogen non-reflector lamps offer high-quality light and are easy to install, replace and operate. All halogen non-reflector lamps incorporate a distortion-free quartz bulb and a precise positioning of the mounted filament. These ensure optimal beam performance and consistent, high light output. A wide range of wattages is available for a broad variety of applications, including projection systems. In addition you get all the proven advantages of halogen technology such as a full spectrum and a color rendering index (CRI) of 100 – the same as natural light and the best that it can be. Halogen lamps also create a comfortable warm white light, and they maintain their lumen output, with almost no reduction, throughout their lifetime.

## Product data

### • General Characteristics

|                      |                |
|----------------------|----------------|
| Philips Code         | 5761           |
| ANSI Code            | -              |
| LIF Code             | -              |
| Cap-Base             | G4             |
| Bulb Material        | Quartz-UV Open |
| Operating Position   | any            |
| Main Application     | Projection     |
| Life to 50% failures | 100 hr         |

### • Electrical Characteristics

|              |      |
|--------------|------|
| Lamp Wattage | 30 W |
| Voltage      | 6 V  |

### • Light Technical Characteristics

|                             |         |
|-----------------------------|---------|
| Color Rendering Index       | 100 Ra8 |
| Color Temperature Technical | 3200 K  |
| Luminous Flux Lamp EM       | 765 Lm  |

### • Product Dimensions

|                       |                |
|-----------------------|----------------|
| Overall Length C      | 31 (max) mm    |
| Diameter D            | 9 (max) mm     |
| Light Center Length L | 19.75 (max) mm |

|                                |         |
|--------------------------------|---------|
| Filament Dimensions (WxH) [mm] | 1.5x1.5 |
|--------------------------------|---------|


### • Luminaire Design Requirements

|                   |             |
|-------------------|-------------|
| Pinch Temperature | 400 (max) C |
| Bulb Temperature  | 900 (max) C |

### • Product Data


|   |                           |
|---|---------------------------|
| Order code                              | 923931110103              |
| Full product code                       | 923931110103              |
| Full product name                       | 5761 30W G4 6V 1CT        |
| Order product name                      | 5761 30W G4 6V 1CT/10X10F |
| Pieces per pack                         | 1                         |
| Packing configuration                   | 10X10F                    |
| Packs per outerbox                      | 100                       |
| Bar code on pack - EAN1                 | 8711500410849             |
| Bar code on intermediate packing - EAN2 | 8711500420923             |
| Bar code on outerbox - EAN3             | 8711500423344             |
| Logistic code(s) - 12NC                 | 923931110103              |
| Net weight per piece                    | 1.300 gr                  |

## Dimensional drawing



### G4

| Product        | C (Max) | D (Max) | L (Max) |
|----------------|---------|---------|---------|
| 5761 30W G4 6V | 31      | 9       | 19.75   |



© 2011 Koninklijke Philips Electronics N.V.  
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

[www.philips.com/lighting](http://www.philips.com/lighting)

2011, August 26  
data subject to change