



Actinic BL TL-D(K) Secura

Actinic BL TL-D TL-DK Secura 36W/10 1SL/25

With an optimized spectrum matching the eye sensitivity of the housefly, Actinic BL TL-D(K) Secura lamps are perfect for attracting insects. They have virtually no UV-B output, and so are perfectly safe. In addition, they have a special "Secura" sleeve that keeps all glass and components together in the case of accidental breakage. This eliminates the risk of glass splinters showering down on food preparation areas, for example. And that is why it meets the strict HACCP requirements. What's more, with the lowest mercury content in the industry and being 100% lead-free, these lamps represent a very good environmental choice.

Product data

General Information		Voltage (Nom)	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]	50 V	
Main Application	Reprography (R)	Approval and Application	
Life to 50% Failures (Nom)	9000 h	Mercury (Hg) Content (Nom)	8.0 mg
Useful Life (Nom)	5000 h	UV	
Light Technical		UV-B/UV-A (IEC)	0.2 %
Color Code	10	UV-A Radiation 100Hr (IEC)	8.8 W
Color Designation	Actinic	Product Data	
Chromaticity Coordinate X (Nom)	225	Full product code	872790086085600
Chromaticity Coordinate Y (Nom)	230	Order product name	Actinic BL TL-D TL-DK Secura 36W/10 1SL/25
UV Depreciation at 2000 h	20 %	EAN/UPC - Product	8727900860856
UV Depreciation at 5000 h	30 %	Order code	928019801003
Operating and Electrical		Numerator - Quantity Per Pack	1
Power (Rated) (Nom)	36 W	Numerator - Packs per outer box	25
Lamp Current (Nom)	0.865 A	Material Nr. (12NC)	928019801003

Actinic BL TL-D(K) Secura

Net Weight (Piece)	127.500 g
--------------------	-----------

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing

Product	D (max)	A (max)	B (max)	B (min)	C (max)
Actinic BL TL-D TL-DK	28 mm	589.8 mm	596.9 mm	594.5 mm	604 mm
Secura 36W/10 1SL/25					

TL-DK Secura 36W/10

Photometric data

Lightcolor /10

Lightcolor /10

