

# HMI DIGITAL 2500 W

HMI DIGITAL | Metal halide lamps, single-ended



#### Areas of application

- Studio
- Stage
- TV

## Product family benefits

- Suited for both analog and digital film production
- Robust stems, resulting in less breakage during transport
- Round moly-foil construction that evenly distributes heat and current extends for lamp longevity (6,000-18,000 W)
- Splash-proof carrying case is re-usable and allows lamps to be transported safely (6,000-18,000 W)

#### **Product family features**

- High CRI of >90
- UV-Stop (UVS)
- Color temperature of 6,000 K (daylight)
- Extremely bright light of up to 100 lumens/watt
- Hot restart capability







## Product datasheet

## Technical data

## **Electrical data**

Nominal wattage	2500.00 W
Nominal voltage	118 V
Nominal current	24.5 A

## Photometrical data

Nominal luminous flux	220 lm
Color temperature	6300 K
Color rendering index Ra	90

## Dimensions & weight

Diameter	60.9 mm
Length	225.0 mm

## Additional product data

Base (standard designation)	G38

### Product datasheet

#### Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, HMI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899984295	HMI DIGITAL 2500 W	Shipping carton box 1	314 mm x 153 mm x 152 mm	7.30 dm <sup>3</sup>	539.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.