

HPL

High-performance lamps




Product family benefits


- Optimum use of the generated light in the spotlight



Product family datasheet



Product line drawing



Product line drawing

Product family datasheet

Technical data

Product description	Product information	Electrical data	Photometrical data		Dimensions & weight				
	Order reference	Nominal voltage	Nominal luminous flux	Color temperature	Diameter	Length	Length with base excl. base pins/connection	Light center length (LCL)	Illuminated field
HPL 93728 575 W 230 V	93728 575W G9.5	230 V	14900 lm	3200 K	19.0 mm	104.0 mm	98.00 mm	60.3 mm	9.5*11.5 mm ^{2 1)}
HPL 93728 575 W 240 V	93728 575W G9.5	240 V	14900 lm	3200 K	19.0 mm	104.0 mm	98.00 mm	60.3 mm	9.5*11.5 mm ^{2 1)}
HPL 93728 LL 575 W 230 V	93728 LL	230 V	11780 lm	3050 K	19.0 mm	104.0 mm	98.00 mm	60.3 mm	14.5*11.0 mm ^{2 1)}
HPL 93728 LL 575 W 240 V	93728 LL	240 V	11780 lm	3050 K	19.0 mm	104.0 mm	98.00 mm	60.3 mm	14.0*14.0 mm ^{2 1)}
HPL 93729 750 W 230 V	750W G9.5 W/HSI	230 V	19750 lm	3200 K	19.0 mm	104.0 mm	104.00 mm	60.3 mm	7.5*11.5 mm ^{2 1)}
HPL 93729 750 W 240 V	93729 750W 240V	240 V	19750 lm	3200 K	19.0 mm	104.0 mm	104.00 mm	60.3 mm	7.5*11.5 mm ^{2 1)}
HPL 93729 LL 750 W 230 V	93729 LL	230 V	15600 lm	3050 K	19.0 mm	104.0 mm	104.00 mm	60.3 mm	15.5*11.0 mm ^{2 1)}
HPL 93729 LL 750 W 240 V	93729 LL	240 V	15600 lm	3050 K	19.0 mm	104.0 mm	104.00 mm	60.3 mm	15.5*11.0 mm ^{2 1)}

Product description	Filament diameter	Lifespan	Additional product data	Capabilities	Certificates & standards	Country specific categorizations
		Lifespan	Base (standard designation)	Burning position	EEI – Energy Label	ANSI code
HPL 93728 575 W 230 V	11.5 mm	400 h	G9.5	Any	B	Other
HPL 93728 575 W 240 V	11.5 mm	400 h	G9.5	Any	C	Other
HPL 93728 LL 575 W 230 V	11.0 mm	1500 h	G9.5	Any	B	Other
HPL 93728 LL 575 W 240 V	14.0 mm	1500 h	G9.5	Any	C	Other
HPL 93729 750 W 230 V	11.5 mm	300 h	G9.5	Any	B	Other
HPL 93729 750 W 240 V	11.5 mm	300 h	2 pins	Any	B	Other
HPL 93729 LL 750 W 230 V	11.0 mm	1500 h	G9.5	Any	C	Other
HPL 93729 LL 750 W 240 V	11.0 mm	1500 h	2 pins	Any	C	Other

Product family datasheet

¹⁾ Type of filament 6-C8

Product family datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (cover panel etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. Because of the heat produced only heat-resistant lamp connections (holders) may be used. Do not operate near people, or any materials that are flammable, sensitive to heat or affected by drying out. Detailed information is available on request.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.