



MSD

MSD 200/2 1CT/4

These single ended, compact lamps enable optimal light collection and accurate beam control, while they also provide true daylight color temperatures – all to create great stage brightness and vivid entertainment. And since they offer long lifetime usage they help minimize the cost of ownership via fewer lamp replacements and fewer maintenance man hour costs.

Product data


General Information	
Cap-Base	GY9.5 [GY9.5]
Operating Position	UNIVERSAL [Any or Universal (U)]
Main Application	Studio/Disco
Life to 50% Failures (Nom)	3000 h
System Description	-
Light Technical	
Color Code	670 (2)
Luminous Flux (Min)	11500 lm
Luminous Flux (Nom)	13500 lm
Chromaticity Coordinate X (Nom)	312
Chromaticity Coordinate Y (Nom)	311
Correlated Color Temperature (Nom)	6700 K
Luminous Efficacy (rated) (Nom)	67 lm/W
Color Rendering Index (Nom)	70
Operating and Electrical	
Power (Nom)	200 W
Lamp Current (Nom)	3.4 A
Ignition Supply Voltage (Min)	207 V

Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Cap-Base Information	-
Luminaire Design Requirements	
Bulb Temperature (Max)	500 °C
Pinch Temperature (Max)	350 °C
Product Data	
Full product code	871869641590000
Order product name	MSD 200/2 1CT/4
EAN/UPC - Product	8718696415900
Order code	928097605115
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	928097605115
Net Weight (Piece)	22.000 g

MSD

Warnings and Safety

Dimensional drawing



MSD 200/2

Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
MSD	23 mm	5.0	54 mm	56 mm	55	108 mm	29 mm	28	27 mm
200/2		mm			mm			mm	
1CT/4									

Photometric data

