



# MSD Platinum (Touring/Stage)

## MSD Platinum 12 R LL UNP/24

The MSD Platinum lamps open up new levels of creative freedom in entertainment lighting, with powerful, compact and brilliantly intense light. Their compact, lightweight design provides the freedom to create smaller, lighter luminaires – for use at any location on stage. And their short arc, high color temperature and innovative reflector produce a sparkling, high beam intensity for outstanding color reproduction. They also offer long and reliable lifetime, high efficacy and fast replacement times. It all adds up to an intensely exciting creative experience.

### Product data

General Information		Correlated Color Temperature (Nom)	
Cap-Base	- [-]	7800 K	
Operating Position	UNIVERSAL [ Any or Universal (U)]	Operating and Electrical	
Main Application	Stage/Touring	Power (Nom)	260 W
Life to 50% Failures (Nom)	2000 h	Voltage (Max)	80 V
Life to 50% Failures entertainment cycle (Nom)	6000 h	Voltage (Min)	55 V
System Description	Reflector-E20.6	Controls and Dimming	
Light Technical		Dimmable	Yes
Color Code	2	Mechanical and Housing	
Luminous Flux (Min)	15000 lm	Cap-Base Information	-
Luminous Flux (Nom)	17100 lm	Luminaire Design Requirements	
Chromaticity Coordinate X (Max)	318	Pinch Temperature (Max)	350 °C
Chromaticity Coordinate X (Min)	285	Product Data	
Chromaticity Coordinate X (Nom)	303	Full product code	871869968356600
Chromaticity Coordinate Y (Max)	324		
Chromaticity Coordinate Y (Min)	294		
Chromaticity Coordinate Y (Nom)	309		


## MSD Platinum (Touring/Stage)

Order product name	MSD Platinum 12 R LL UNP/24
EAN/UPC - Product	8718699683566
Order code	928496705308
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	24

Material Nr. (12NC)	928496705308
Net Weight (Piece)	72.000 g

### Warnings and Safety

### Dimensional drawing



MSD Platinum 12 R LL

Product	D (max)	T (max)	O	C (max)
MSD Platinum 12 R LL UNP/24	51.5 mm	6.8 mm	0.95 mm	57.1 mm

### Photometric data

