



# MSD Platinum (Touring/Stage)

## MSD Platinum 200 Flex UNP/24

The MSD Platinum lamps open up new levels of creative freedom in entertainment lighting, with powerful, compact and brilliantly intense light. Their compact, lightweight design provides the freedom to create smaller, lighter luminaires – for use at any location on stage. And their short arc, high color temperature and innovative reflector produce a sparkling, high beam intensity for outstanding color reproduction. They also offer long and reliable lifetime, high efficacy and fast replacement times. It all adds up to an intensely exciting creative experience.

### Product data

General Information	
Cap-Base	- [-]
Operating Position	UNIVERSAL [ Any or Universal (U)]
Life to 50% Failures (Nom)	2000 h
Life to 50% Failures entertainment cycle (Nom)	6000 h

Light Technical	
Color Code	2
Luminous Flux (Nom)	12000 lm
Chromaticity Coordinate X (Nom)	0.300
Chromaticity Coordinate Y (Nom)	0.305
Correlated Color Temperature (Nom)	7800 K

Operating and Electrical	
Power (Nom)	240 W
Voltage (Min)	55 V

Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Cap-Base Information	-



Luminaire Design Requirements	
Pinch Temperature (Max)	350 °C

Product Data	
Full product code	871869680817700
Order product name	MSD Platinum 200 Flex UNP/24
EAN/UPC - Product	8718696808177
Order code	928495705308
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	24
Material Nr. (12NC)	928495705308
Net Weight (Piece)	71.200 g

# MSD Platinum (Touring/Stage)

## Warnings and Safety

## Dimensional drawing



Product	D (max)	O	C (max)	T
MSD Platinum 200 Flex UNP/24	56.5 mm	0.8 mm	60 mm	7 mm

MSD Platinum 200 Flex

## Photometric data

