



# MSD Platinum (Touring/Stage)

## MSD Platinum 300S Flex UNP/24

The MSD Platinum lamps open up new levels of creative freedom in entertainment lighting, with powerful, compact and brilliantly intense light. Their compact, lightweight design provides the freedom to create smaller, lighter luminaires – for use at any location on stage. And their short arc, high color temperature and innovative reflector produce a sparkling, high beam intensity for outstanding color reproduction. They also offer long and reliable lifetime, high efficacy and fast replacement times. It all adds up to an intensely exciting creative experience.

### Product data

General Information		Color Rendering Index (Nom)	
Cap-Base	- [-]		-
Operating Position	UNIVERSAL [ Any or Universal (U)]	Operating and Electrical	
Main Application	Stage/Touring	Power (Nom)	370 W
Life to 50% Failures (Nom)	1500 h	Voltage (Max)	110 V
Life to 50% Failures entertainment cycle (Nom)	6000 h	Voltage (Min)	75 V
Light Technical		Controls and Dimming	
Color Code	2	Dimmable	Yes
Luminous Flux (Min)	20900 lm	Mechanical and Housing	
Luminous Flux (Nom)	23200 lm	Cap-Base Information	-
Chromaticity Coordinate X (Max)	315	Luminaire Design Requirements	
Chromaticity Coordinate X (Min)	285	Bulb Temperature (Max)	900 °C
Chromaticity Coordinate X (Nom)	300	Pinch Temperature (Max)	350 °C
Chromaticity Coordinate Y (Max)	315		
Chromaticity Coordinate Y (Min)	285		
Chromaticity Coordinate Y (Nom)	300		
Correlated Color Temperature (Nom)	8000 K		

# MSD Platinum (Touring/Stage)


## Product Data

Full product code	871869965192300
Order product name	MSD Platinum 300S Flex UNP/24
EAN/UPC - Product	8718699651923
Order code	928496305308
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	24
Material Nr. (12NC)	928496305308
Net Weight (Piece)	101.000 g

## Warnings and Safety

## Dimensional drawing



MSD Platinum 300 Flex

Product	D (max)	O	C (max)
MSD Platinum 300S Flex UNP/24	58.5 mm	1.0 mm	66.4 mm

## Photometric data

