



# MSR

## MSR 1200/2.1CT/3

The high color rendering index of the single ended MSR series ensures that everyone in the audience can enjoy the true colors of the scenery, the stage props, the players and their costumes – in fact everything that is on stage can be made bright and vivid in daylight quality light. Also, thanks to the single ended lamp concept, the luminaire has optimal light collection and direction possibilities to help ensure brightness on stage exactly where and when it is needed. In addition, the MSR can be used in any burning position for easy set-up and convenience.

### Product data


General Information	
Cap-Base	G22 [ G22]
Operating Position	UNIVERSAL [ Any or Universal (U)]
Main Application	Studio/Disco
Life to 50% Failures (Nom)	800 h
System Description	Cold Strike
Light Technical	
Color Code	2
Luminous Flux (Min)	93600 lm
Luminous Flux (Nom)	104000 lm
Chromaticity Coordinate X (Nom)	302
Chromaticity Coordinate Y (Nom)	320
Correlated Color Temperature (Nom)	7200 K
Luminous Efficacy (rated) (Nom)	87 lm/W
Color Rendering Index (Nom)	85
Operating and Electrical	
Power (Nom)	1200 W
Lamp Current (Nom)	13.8 A

Ignition Supply Voltage (Min)	207 V
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Cap-Base Information	30 mm x 53 mm
Luminaire Design Requirements	
Bulb Temperature (Max)	700 °C
Pinch Temperature (Max)	350 °C
Product Data	
Full product code	872790091133600
Order product name	MSR 1200/2.1CT/3
EAN/UPC - Product	8727900911336
Order code	928171805114
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	3
Material Nr. (12NC)	928171805114

Net Weight (Piece)	0.150 kg
--------------------	----------

Warnings and Safety

Dimensional drawing



MSR 1200/2

Product	D (max)	O	L (min)	L (max)	L	C (max)	F
MSR 1200/2.1CT/3	40 mm	10.0 mm	84 mm	86 mm	85 mm	175 mm	53 mm

Photometric data

