



MSR Hot Restrike

MSR 200 HR 1CT/4

Thanks to an optimized color temperature and a high color rendering index, the MSR Hot Restrike creates perfect 'daylight' in any condition. Also, the single ended lamp design enables hot re-ignition, which ensures daylight lighting and superb color rendition is always instantly available. They also incorporate the innovative P3 technology, developed by Philips, which allows use at higher temperatures and therefore extends lifetime and consistency of high-quality light output.


Product data

General Information	
Cap-Base	GZY9.5 [GZY9.5]
Operating Position	UNIVERSAL [Any or Universal (U)]
Main Application	Studio/Theatre
Life to 50% Failures (Nom)	200 h
System Description	Hot Restrike
Light Technical	
Color Code	- [Not Specified]
Luminous Flux (Min)	12000 lm
Luminous Flux (Nom)	15000 lm
Chromaticity Coordinate X (Nom)	325
Chromaticity Coordinate Y (Nom)	323
Correlated Color Temperature (Nom)	6000 K
Luminous Efficacy (rated) (Nom)	75 lm/W
Color Rendering Index (Nom)	92
Operating and Electrical	
Power (Nom)	200 W
Lamp Current (Nom)	3.3 A

Ignition Supply Voltage (Min)	207 V
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Cap-Base Information	-
Luminaire Design Requirements	
Bulb Temperature (Max)	700 °C
Pinch Temperature (Max)	350 °C
Product Data	
Full product code	871869641604400
Order product name	MSR 200 HR 1CT/4
EAN/UPC - Product	8718696416044
Order code	928097905115
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	928097905115
Net Weight (Piece)	22.000 g

Warnings and Safety



Dimensional drawing



MSR 200 HR

Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
MSR 200	20 mm	5.0	38 mm	40 mm	39	80 mm	24 mm	23.5	23 mm
HR 1CT/4		mm			mm			mm	

Photometric data



XDPO_XDMSR_HR--Spectral power distribution Colour

