



MSR

MSR 400 1CT/4

The high color rendering index of the single ended MSR series ensures that everyone in the audience can enjoy the true colors of the scenery, the stage props, the players and their costumes – in fact everything that is on stage can be made bright and vivid in daylight quality light. Also, thanks to the single ended lamp concept, the luminaire has optimal light collection and direction possibilities to help ensure brightness on stage exactly where and when it is needed. In addition, the MSR can be used in any burning position for easy set-up and convenience.

Product data


| General Information | |
|------------------------------------|-----------------------------------|
| Cap-Base | GX9.5 [GX9.5] |
| Operating Position | UNIVERSAL [Any or Universal (U)] |
| Main Application | Studio/Disco |
| Life to 50% Failures (Nom) | 1000 h |
| System Description | Cold Strike |
| Light Technical | |
| Color Code | - [Not Specified] |
| Luminous Flux (Min) | 28500 lm |
| Luminous Flux (Nom) | 32000 lm |
| Chromaticity Coordinate X (Nom) | 325 |
| Chromaticity Coordinate Y (Nom) | 320 |
| Correlated Color Temperature (Nom) | 5900 K |
| Luminous Efficacy (rated) (Nom) | 80 lm/W |
| Color Rendering Index (Nom) | 95 |
| Operating and Electrical | |
| Power (Nom) | 400 W |
| Lamp Current (Nom) | 6.9 A |

| Ignition Supply Voltage (Min) | 207 V |
|---------------------------------|-----------------|
| Controls and Dimming | |
| Dimmable | No |
| Mechanical and Housing | |
| Cap-Base Information | - |
| Luminaire Design Requirements | |
| Bulb Temperature (Max) | 700 °C |
| Pinch Temperature (Max) | 350 °C |
| Product Data | |
| Full product code | 871869641600600 |
| Order product name | MSR 400 1CT/4 |
| EAN/UPC - Product | 8718696416006 |
| Order code | 928077905115 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 4 |
| Material Nr. (12NC) | 928077905115 |

| | |
|--------------------|----------|
| Net Weight (Piece) | 44.000 g |
|--------------------|----------|

Warnings and Safety

Dimensional drawing



| Product | D (max) | O | L (min) | L (max) | L | C (max) | F (max) | F | F (min) |
|---------|---------|-----|---------|---------|----|---------|---------|----|---------|
| MSR 400 | 23 mm | 6.0 | 61 mm | 63 mm | 62 | 112 mm | 36 mm | 35 | 34 mm |
| 1CT/4 | | mm | | | mm | | | mm | |

MSR 400

Photometric data

