



# MSR

## MSR 575/2 10H 1CT/4

The high color rendering index of the single ended MSR series ensures that everyone in the audience can enjoy the true colors of the scenery, the stage props, the players and their costumes – in fact everything that is on stage can be made bright and vivid in daylight quality light. Also, thanks to the single ended lamp concept, the luminaire has optimal light collection and direction possibilities to help ensure brightness on stage exactly where and when it is needed. In addition, the MSR can be used in any burning position for easy set-up and convenience.

### Product data


<b>GeniPubl</b>		<b>6.75 A</b>		<b>6.75 A</b>	
<b>GX9.5   GX9.5</b>	GX9.5 [ GX9.5]	<b>207 V</b>		<b>207 V</b>	
<b>UNIVERSAL   Any or Universal (U)</b>		<b>UNIVERSAL   Any or Universal (U)</b>			
<b>Studio/Disco</b>	Studio/Disco	<b>CntrPubl</b>			
<b>1000 h</b>	1000 h	<b>No</b>		<b>No</b>	
<b>Cold Strike</b>	Cold Strike	<b>MechPubl</b>			
<b>LittPubl</b>		<b>20 mm</b>		<b>20 mm</b>	
<b>2</b>	2	<b>LDRPubl</b>			
<b>42750 lm</b>	42750 lm	<b>700 °C</b>		<b>700 °C</b>	
<b>47500 lm</b>	47500 lm	<b>350 °C</b>		<b>350 °C</b>	
<b>302</b>	302	<b>ProductPubl</b>			
<b>320</b>	320	<b>871829122127200</b>		<b>871829122127200</b>	
<b>6990 K</b>	6990 K	<b>MSR 575/2 10H 1CT/4</b>		<b>MSR 575/2 10H 1CT/4</b>	
<b>75 lm/W</b>	75 lm/W	<b>8718291221272</b>		<b>8718291221272</b>	
<b>83 lm/W</b>	83 lm/W	<b>928171605115</b>		<b>928171605115</b>	
<b>70</b>	70	<b>1</b>		<b>1</b>	
<b>ElecPubl</b>		<b>4</b>		<b>4</b>	
<b>575 W</b>	575 W				

# MSR

928171605115	928171605115
0.057 kg	0.057 kg

## Warnings and Safety

### Dimensional drawing



Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
MSR 575/2	30 mm	7.0	64 mm	66 mm	65	125 mm	36 mm	35	34 mm
10H 1CT/4		mm			mm			mm	

MSR 575/2 10H

### Photometric data

