



# MSR Short Arc

## MSR 700 SA 1CT/4

The lamp's short arc and compact design helps enable a compact luminaire that provides high beam intensity, while the excellent color rendition characteristics help ensure optimal colors on stage. The highly innovative P3 technology, developed by Philips, allows MSR Short Arc lamps to be used at higher temperatures in any burning position. The result? Longer lifetime, fewer early failures and a highly consistent performance throughout the lamp's lifetime.

### Product data


General Information	
Cap-Base	GY9.5 [ GY9.5]
Operating Position	UNIVERSAL [ Any or Universal (U)]
Main Application	Studio/Disco
Life to 50% Failures (Nom)	750 h
System Description	Short Arc
Light Technical	
Color Code	- [ Not Specified]
Luminous Flux (Min)	49500 lm
Luminous Flux (Nom)	55000 lm
Chromaticity Coordinate X (Nom)	333
Chromaticity Coordinate Y (Nom)	342
Correlated Color Temperature (Nom)	5600 K
Luminous Efficacy (rated) (Nom)	78 lm/W
Color Rendering Index (Nom)	80
Operating and Electrical	
Power (Nom)	700 W
Lamp Current (Nom)	11 A

Ignition Supply Voltage (Min)	207 V
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Cap-Base Information	-
Luminaire Design Requirements	
Bulb Temperature (Max)	1000 °C
Pinch Temperature (Max)	500 °C
Product Data	
Full product code	871829122802800
Order product name	MSR 700 SA 1CT/4
EAN/UPC - Product	8718291228028
Order code	928170305115
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	928170305115
Net Weight (Piece)	0.020 kg

# MSR Short Arc

## Warnings and Safety


### Dimensional drawing



MSR 700 SA

Product	D (max)	O	L (min)	L (max)	L	C (max)
MSR 700 SA 1CT/4	25 mm	4.0 mm	38 mm	40 mm	39 mm	83 mm

### Photometric data



XDPB\_XDMSR\_SA-Spectral power distribution B/W

