



# MSR Gold™ MiniFastFit (Touring/ Stage)

## MSR Gold™ 1000 MiniFastFit 1CT/4

Thanks to the specially designed lamp base, the MSR Gold™ MiniFastFit takes just seconds to replace, to help ensure non-stop clubbing entertainment. In addition, the innovative gold plated pins ensure excellent current transfer to prolong lamp and lamp holder lifetimes and thereby reduce lamp replacement costs. Easy handling and small compact fixture designs are allowed by the lamps compact size, while the very short arc provides a high perceived brightness and high beam intensity.

### Product data

General Information		Color Rendering Index (Nom)	
Cap-Base	PGJX36 [ PGJX36]		80
Operating Position	UNIVERSAL [ Any or Universal (U)]	Operating and Electrical	
Main Application	Entertainment	Power (Nom)	1000.0 W
Life to 50% Failures (Nom)	900 h	Lamp Current (Nom)	11.4 A
System Description	MiniFastFit	Ignition Supply Voltage (Min)	198 V
Light Technical		Controls and Dimming	
Color Code	- [ Not Specified]	Dimmable	Yes
Luminous Flux (Min)	74000 lm	Mechanical and Housing	
Luminous Flux (Nom)	82000 lm	Cap-Base Information	PGJX36
Chromaticity Coordinate X (Nom)	0.321	Luminaire Design Requirements	
Chromaticity Coordinate Y (Nom)	0.330	Bulb Temperature (Max)	950 °C
Correlated Color Temperature (Nom)	6000 K		
Luminous Efficacy (rated) (Nom)	82 lm/W		


## MSR Gold™ MiniFastFit (Touring/Stage)

Pinch Temperature (Max)	500 °C
<b>Product Data</b>	
Full product code	871829178508800
Order product name	MSR Gold™ 1000 MiniFastFit 1CT/4
EAN/UPC - Product	8718291785088
Order code	928171405115

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	928171405115
Net Weight (Piece)	0.055 kg

### Warnings and Safety

### Dimensional drawing



MSR GOLD 1000 MiniFastFit

Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
MSR Gold™ 1000 MiniFastFit 1CT/4	26 mm	5.5 mm	55 mm	57 mm	56 mm	112 mm	36.5 mm	36 mm	35.3 mm

