



MSR Gold™ FastFit

MSR Gold™ 1500 FastFit 1CT/4

All lamps burn out eventually, but when this happens with single ended MSR Gold™ FastFit, it is replaced in seconds – thanks to the specially designed lamp base and lamp holder. This lamp provides a high beam intensity of pure, white light for a truly illuminating performance, while the gold-plated caps provide superior heat protection and prevent premature failure. P3 technology allows use in any position and at higher temperatures, further extending lamp life and consistency of high-quality light output. Also, because the FastFit design is applied to Philips Halogen lamps, switching between lamp technologies can be done quickly and easily. The Philips MSR Gold™ FastFit can be operated in a lamp wattage range between 700W and 2500W.

Product data

General Information	
Cap-Base	PGJX50 [PGJX50]
Operating Position	UNIVERSAL [Any or Universal (U)]
Main Application	Entertainment
Life to 50% Failures (Nom)	750 h
System Description	FastFit
Light Technical	
Luminous Flux (Min)	100600 lm
Luminous Flux (Nom)	120000 lm
Chromaticity Coordinate X (Nom)	323
Chromaticity Coordinate Y (Nom)	333
Correlated Color Temperature (Nom)	6000 K
Luminous Efficacy (rated) (Nom)	80 lm/W
Color Rendering Index (Nom)	80

Operating and Electrical	
Power (Rated) (Nom)	1500 W
Lamp Current (Nom)	15.3 A
Ignition Supply Voltage (Min)	198 V

Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Cap-Base Information	PGJX50

Luminaire Design Requirements	
Bulb Temperature (Max)	950 °C
Pinch Temperature (Max)	500 °C

Product Data	
Full product code	871829122134000

MSR Gold™ FastFit


Order product name	MSR Gold™ 1500 FastFit 1CT/4
EAN/UPC - Product	8718291221340
Order code	928107305115
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4

Material Nr. (12NC)	928107305115
Net Weight (Piece)	0.131 kg

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


Dimensional drawing




MSR GOLD 1500 FastFit

Product	D (max)	O	L (min)	L (max)	L	C (max)	F
MSR Gold™ 1500 FastFit 1CT/4	28 mm	6.3 mm	64 mm	66 mm	65 mm	128 mm	50 mm

Photometric data



MSR Gold™ 1500 FastFit



MSR Gold™ 1500 FastFit

