



# MSR Gold™ SA Double Ended

## MSR Gold™ 1510 SA/1 DE 1CT/4

To optimize the total lifetime of the double ended MSR Gold™ SA Double Ended lamps, the caps are plated with gold. This provides superior heat protection and thereby minimizes premature failure of the lamp and lamp holder, as well as ensuring extended consistent performance. In addition, the highly innovative P3 technology, developed by Philips, allows the lamp to be used at higher temperatures, which further extends service life and consistency of high-quality light output.

### Product data

|   |                                   |                                     |                              |
|---|-----------------------------------|-------------------------------------|------------------------------|
| <b>GeniPubl</b>                         |                                   | <b>13.4 A</b>                       | 13.4 A                       |
| <b>SFC10-4   SFC10-4</b>                | SFC10-4 [ SFC10-4]                | <b>198 V</b>                        | 198 V                        |
| <b>UNIVERSAL   Any or Universal (U)</b> | UNIVERSAL [ Any or Universal (U)] | <b>CntrPubl</b>                     |                              |
| <b>Entertainment</b>                    | Entertainment                     | <b>Yes</b>                          | Yes                          |
| <b>750 h</b>                            | 750 h                             | <b>MechPubl</b>                     |                              |
| <b>SA/DE</b>                            | SA/DE                             | <b>SFC10-4</b>                      | SFC10-4                      |
| <b>LittPubl</b>                         |                                   | <b>LDRPubl</b>                      |                              |
| <b>-   Not Specified</b>                | - [ Not Specified]                | <b>950 °C</b>                       | 950 °C                       |
| <b>141000 lm</b>                        | 141000 lm                         | <b>450 °C</b>                       | 450 °C                       |
| <b>330</b>                              | 330                               | <b>ProductPubl</b>                  |                              |
| <b>338</b>                              | 338                               | <b>871869653613100</b>              | 871869653613100              |
| <b>5600 K</b>                           | 5600 K                            | <b>MSR Gold™ 1510 SA/1 DE 1CT/4</b> | MSR Gold™ 1510 SA/1 DE 1CT/4 |
| <b>94 lm/W</b>                          | 94 lm/W                           | <b>8718696536131</b>                | 8718696536131                |
| <b>90</b>                               | 90                                | <b>928410005115</b>                 | 928410005115                 |
| <b>ElecPubl</b>                         |                                   |                                     |                              |
| <b>1510 W</b>                           | 1510 W                            |                                     |                              |


# MSR Gold™ SA Double Ended

|              |              |
|--------------|--------------|
| 1            | 1            |
| 4            | 4            |
| 928410005115 | 928410005115 |

|          |          |
|----------|----------|
| 34.000 g | 34.000 g |
|----------|----------|

## Warnings and Safety



## Dimensional drawing



MSR GOLD 1510 SA/1 DE

| Product                         | A (max)  | A (min)  | A        | C (max) | D (max) | O    |
|---------------------------------|----------|----------|----------|---------|---------|------|
| MSR Gold™ 1510 SA/1 DE<br>1CT/4 | 115.2 mm | 114.4 mm | 114.8 mm | 136 mm  | 23 mm   | 7 mm |

## Photometric data



XDPO\_XDMSR\_SADE-Spectral power distribution Colour

