



MSR Gold™ FastFit

MSR Gold™ 2000/2 FastFit 1CT/8

All lamps burn out eventually, but when this happens with single ended MSR Gold™ FastFit, it is replaced in seconds – thanks to the specially designed lamp base and lamp holder. This lamp provides a high beam intensity of pure, white light for a truly illuminating performance, while the gold-plated caps provide superior heat protection and prevent premature failure. P3 technology allows use in any position and at higher temperatures, further extending lamp life and consistency of high-quality light output. Also, because the FastFit design is applied to Philips Halogen lamps, switching between lamp technologies can be done quickly and easily. The Philips MSR Gold™ FastFit can be operated in a lamp wattage range between 700W and 2500W.

Product data

| General Information | |
|------------------------------------|-----------------------------------|
| Cap-Base | PGJX50 [PGJX50] |
| Operating Position | UNIVERSAL [Any or Universal (U)] |
| Main Application | Entertainment |
| Life to 50% Failures (Nom) | 750 h |
| System Description | FastFit |
| Light Technical | |
| Color Code | 2 |
| Luminous Flux (Min) | 138000 lm |
| Luminous Flux (Nom) | 160000 lm |
| Chromaticity Coordinate X (Nom) | 297 |
| Chromaticity Coordinate Y (Nom) | 322 |
| Correlated Color Temperature (Nom) | 7500 K |
| Luminous Efficacy (rated) (Nom) | 80 lm/W |
| Color Rendering Index (Nom) | 88 |

| Operating and Electrical | |
|-------------------------------|-----------------|
| Power (Nom) | 2000 W |
| Lamp Current (Nom) | 15.4 A |
| Ignition Supply Voltage (Min) | 198 V |
| Controls and Dimming | |
| Dimmable | Yes |
| Mechanical and Housing | |
| Cap-Base Information | PGJX50 |
| Luminaire Design Requirements | |
| Bulb Temperature (Max) | 950 °C |
| Pinch Temperature (Max) | 500 °C |
| Product Data | |
| Full product code | 872790090830500 |


MSR Gold™ FastFit

| | |
|---------------------------------|--------------------------------|
| Order product name | MSR Gold™ 2000/2 FastFit 1CT/8 |
| EAN/UPC - Product | 8727900908305 |
| Order code | 928106105114 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 8 |

| | |
|---------------------|--------------|
| Material Nr. (12NC) | 928106105114 |
| Net Weight (Piece) | 0.147 kg |

Warnings and Safety

Dimensional drawing



| Product | D (max) | O | L (min) | L (max) | L | C (max) | F |
|-----------------------------------|---------|--------|---------|---------|-------|---------|-------|
| MSR Gold™ 2000/2 FastFit 1CT/8 | 34 mm | 8.0 mm | 66 mm | 68 mm | 67 mm | 134 mm | 50 mm |

MSR GOLD 2000/2 FastFit

