

Halogen lamps with reflector MR16




Product family features


- Xenon instead of krypton as the filler gas (XENOPHOT HLX versions)
- Luminous flux up to 10 % higher with same power consumption (XENOPHOT HLX versions)



Product family datasheet



Product line drawing



Base

Product family datasheet

Technical data

Product description	Product information	Electrical data		Light technical data	Dimensions & weight		Lifespan	Additional product data	
	Order reference	Nominal voltage	Nominal wattage	Focal length	Diameter	Length	Lifespan	Coating	Base (standard designation)
64607 50 W 8 V	64607 EFM 50W 8	8 V	50.00 W	32.0 mm	51.0 mm	42.0 mm	50 h	Aluminum	GZ6.35
64615 HLX	64615 HLX	12.0 V	75.00 W	32.0 mm	51.0 mm	42.0 mm	50 h	Dichroic	GZ6.35
64619 90 W 14.5 V	64619 90W 14,8V	14.5 V	90.00 W	155.0 mm	51.0 mm	45.0 mm	500 h	True	GX5.3
64627 HLX	64627 HLX	12.0 V	100.00 W	32.0 mm	51.0 mm	42.0 mm	50 h	True	GZ6.35
64629 100 W 12 V	64629 100W 12V	12.0 V	100.00 W	32.0 mm	51.0 mm	42.0 mm	600 h	Dichroic	GZ6.35
64637 100 W 12 V	64637 EBV 100W	12.0 V	100.00 W	32.0 mm	51.0 mm	42.0 mm	1500 h	Dichroic	GZ6.35
64620 150 W 15 V	64620 150W 15V	15.0 V	150.00 W	32.0 mm	51.0 mm	42.0 mm	500 h	Dichroic	GZ6.35
64634 HLX	64634 HLX	15.0 V	150.00 W	32.0 mm	51.0 mm	42.0 mm	50 h	Dichroic	GZ6.35
64635 HLX ¹⁾	64635 HLX	15.0 V	150.00 W	19.0 mm	51.0 mm	45.0 mm	50 h	Gold	GZ6.35
93637 150 W 21 V	93637 150W 21V	21.0 V	150.00 W	44.5 mm	51.0 mm	44.5 mm	100 h	True	GX5.3
93638 150 W 21 V	93638 EKE 150W	21.0 V	150.00 W	44.5 mm	51.0 mm	44.5 mm	200 h	Dichroic	GX5.3
93653 250 W 24 V	93653 250W 24V	24.0 V	250.00 W	35.0 mm	51.0 mm	44.5 mm	300 h	Dichroic	GX5.3
64659 250 W 24 V	64659	24.0 V	250.00 W	35.0 mm	51.0 mm	44.5 mm	1000 h	Dichroic	GX5.3
Hal with Reflector 93506 250 W 120 V	93506	120 V	250.00 W	152.5 mm	51.0 mm	44.5 mm	175 h	Dichroic	GY5.3
Hal with Reflector 93518 300 W 120 V	93518 ELH 300W	120 V	300.00 W	152.5 mm	51.0 mm	45.0 mm	35 h	Dichroic	GY5.3

Product family datasheet

Product description	Minimum diameter of lamp enclosure	Capabilities			Certificates & standards	Country specific categorizations	
		Dimmable	Cooling	Burning position		ANSI code	LIF
64607 50 W 8 V	51.0 mm	Yes	Forced	p90/p15	B	EFM	A1/229
64615 HLX	51.0 mm	Yes	Forced	p90/p15	B	EFN	A1/230
64619 90 W 14.5 V	51.0 mm	Yes	Forced	Other	B	EPX	
64627 HLX	51.0 mm	Yes	Forced	Other	B	EFP	A1/231
64629 100 W 12 V	51.0 mm	Yes	Forced	p90/p15	B	EFP-6	
64637 100 W 12 V				s120	B	EBV	A1/271
64620 150 W 15 V				p90/p15	B	EFR-5	
64634 HLX	51.0 mm	Yes	Forced	p90/p15	B	EFR	A1/232
64635 HLX ¹⁾	51.0 mm	Yes	Forced	Any	B		
93637 150 W 21 V	51.0 mm	Yes	Convection	s90	E	EJV	
93638 150 W 21 V	51.0 mm	Yes	Forced	s90	E	EKE	
93653 250 W 24 V	51.0 mm	Yes	Forced	Any	E	ELC-3	
64659 250 W 24 V				Any	B	ELC-10	
Hal with Reflector 93506 250 W 120 V				s90	E	ENH	
Hal with Reflector 93518 300 W 120 V				s90	E	ELH	

Product description	Photometrical data	
	Nominal luminous flux	Color temperature
64607 50 W 8 V		
64615 HLX		
64619 90 W 14.5 V	43 lm	

Product family datasheet

Product description	Photometrical data	
	Nominal luminous flux	Color temperature
64627 HLX		
64629 100 W 12 V		
64637 100 W 12 V		3000 K
64620 150 W 15 V		3270 K
64634 HLX		
64635 HLX ¹⁾		
93637 150 W 21 V		
93638 150 W 21 V		3300 K
93653 250 W 24 V		
64659 250 W 24 V	400 lm	3200 K
Hal with Reflector 93506 250 W 120 V	340 lm	3150 K
Hal with Reflector 93518 300 W 120 V		

¹⁾ Infra-red lamp; temperature at the focal point approximately 1300 °C

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

References / Links

For further technical information please refer to the following OSRAM brochure:

“Technology and applications, Low-voltage tungsten-halogen lamps”

“Halogen lamps, low and medium voltage for entertainment, technical and medical applications” cross reference list

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.