



Halogen non-reflector

14530 300W GY6.35 24V 1CT/24

Low-voltage quartz halogen capsule lamps

Product data

General Information	
Cap base	GY6.35 [GY6.35]
Philips code	14530
ANSI Code	FLW
LIF code	-
Burning Position	S90 [Standing +/-90D or Base Down (BDH)]
Main application	Projection
Life to 50% failures (nom.)	50 h
Light Technical	
Lamp Luminous Flux (Nom)	10450 lm
Colour Temperature, horizontal (Nom)	3500 K
Colour Rendering Index,horiz (Nom)	100
Operating and Electrical	
Power (Rated) (Nom)	300 W
Voltage (Nom)	24 V
Mechanical and Housing	
Bulb material	Quartz-UV Open

Filament shape	Flat
Filament dimensions WxH	6.7x4.6
Luminaire Design Requirements	
Bulb temperature (max.)	900 °C
Pinch temperature (max.)	400 °C
Product Data	
Full product code	871150042461730
Order product name	14530 300W GY6.35 24V 1CT/24
EAN/UPC – product	8711500424617
Order code	924041420594
Numerator – quantity per pack	1
Numerator – packs per outer box	24
Material no. (12NC)	924041420594
Net weight (piece)	0.006 kg

Halogen non-reflector

Dimensional drawing



Product	D (max)	L (min)	L (max)	L	P (max)	P	P (min)	C (max)
14530 300W	13.5 mm	32.75	33.25	33	1.30 mm	1.25	1.20	55 mm
GY6.35 24V		mm	mm	mm		mm	mm	
1CT/24								

14530 300W GY6.35 24V

