

HBO 12000 W/CHL

HBO-IC | Microlithography lamps for Canon LCD systems




Product datasheet

Technical data

Electrical data

Nominal voltage	112 V
Nominal current	107 A
Type of current	DC
Rated wattage	12000.00 W
Nominal wattage	12000.00 W

Dimensions & weight



Diameter	124.0 mm
Length	500.0 mm
Mounting length	500.0 mm
Length with base excl. base pins/connection	450.00 mm
Light center length (LCL)	200.0 mm ¹⁾
Electrode gap cold	11.0 mm

¹⁾ Distance from end of base to tip of anode or cathode (cold)

Additional product data

Base anode (standard designation)	SFaX46-14/60 ¹⁾
Base cathode (standard designation)	SFa37-16/60

¹⁾ With cable connection (M 10)

Capabilities

Dimmable	No
Cooling	Forced ¹⁾
Burning position	Other ²⁾

¹⁾ Maximum permissible base temperature: 200 °C

²⁾ Anode on top

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321651129	HBO 12000 W/CHL	Shipping carton box 1	340 mm x 340 mm x 900 mm	104.04 dm ³	6596.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.