

HBO 1500 W/CIEL

HBO-IC | Microlithography lamps for Canon i-line systems




Product datasheet

Technical data

Electrical data

Nominal current	62.5 A
Nominal voltage	23.0 V
Type of current	DC
Rated wattage	1500.00 W
Nominal wattage	1500.00 W

Dimensions & weight



Diameter	52.0 mm
Length	262.0 mm
Electrode gap cold	4.0 mm

Capabilities

Dimmable	No
Burning position	Other ¹⁾

¹⁾ Anode underneath

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300538204	HBO 1500 W/CIEL	Shipping carton box 1	510 mm x 420 mm x 420 mm	89.96 dm ³	2234.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.