

HBO 5000 W/S

HBO-IC | Microlithography lamps for Süss systems




Product datasheet

Technical data

Electrical data

Nominal voltage	50.0 V
Nominal current	100 A
Type of current	DC
Rated wattage	5000.00 W
Nominal wattage	5000.00 W

Dimensions & weight



Diameter	80.0 mm
Length	360.0 mm
Length with base excl. base pins/connection	360.00 mm
Light center length (LCL)	143.5 mm ¹⁾
Electrode gap cold	7.5 mm

¹⁾ Distance from end of base to tip of anode or cathode (cold)

Additional product data

Base anode (standard designation)	SFa33.5-9.4/50 ¹⁾
Base cathode (standard designation)	SFa33.5-7.85/50
Product remark	Lamp contains overpressure even in cold status - additional safety regulations, supplied with the lamps, have to be fulfilled. Please read Technical bulletin DO-SEM TB 004 carefully

¹⁾ With cable connection (M 10)

Capabilities

Dimmable	No
Cooling	Forced ¹⁾
Burning position	Other ²⁾

Product datasheet

1) Maximum permissible base temperature: 200 °C / Base cooling

2) Anode on top

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321147875	HBO 5000 W/S	Sliding sleeve 1	- x - x -		1170.00 g
4008321147882	HBO 5000 W/S	Shipping carton box 1	800 mm x 600 mm x 825 mm	396.00 dm ³	16384.00 g
4008321635549	HBO 5000 W/S	Shipping carton box 1	800 mm x 600 mm x 953 mm	457.44 dm ³	16384.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.